

ROYAL GROUT (N)

(Normal free flow Non-shrink High Strength Grout)

Description: Royal Grout N is Normal free flow non-shrink grout specially designed for use where high strength and normal fluidity is required. It is formulated as a natural aggregate fluidity is required. It is formulated as a natural aggregate. Royal Grout is formulated to provide consistency and exacting performance in critical grouting operations. This also can be used as are pair product in various type of application in the protects.

Application: Heavy duty grouting of machinery and equipment

- i) Bridge seals
- ii) Structural columns
- iii) Bending Plates
- iv) Crane Rails

Properties: (i) High fluid and extremely placeable for easy field use

- ii) High Strength for maximum load bending.
- iii) Non-Shrink with minimum positive expansion for high expansion in for high tolerance.
- iv) Rapid strength gain to minimum turn, around time for equipment regrouets.
- v) Excellent working time at high ambient temperature.

Technical Data:

Colour	-	Grey
Form	-	Powder
Flow Rate	-	10-15 cm
Pot Life (workability)	-	50-60 minute

Health & safety: use goggles and hand gloves during application.

- ii) Clean hand with warm soap water after application

iii) Do not use solvent to clean the contact area.

Storage: Must be stored in original packing, in ambient temperature dry place under shed. Protect from direct sunlight.

IMPORTANT

The product are manufactured under stringent quality standard specification and guaranteed against any manufacturing defect based our practical experience and exposure, and are believed to be most appropriate and correct. But no liability can be accepted by us as the condition of use of such products are beyond our control. The user is expected to check, the suitability of particular product for his intended uses