

ROYAL PLAST HR

(High Range Concrete Super Plasticizer)

Description: Royal Plast HR is a high range water reducing admixture to super plasticizer for producing high performance and free flowing concrete. It is brown colour liquid based on organic polymers. It allows large water reduction upto 20% is possible with Royal HR depending upon the dose.

Application: Mix design as normally required for super plasticizer should be followed with Royal Plast HR for the particulars requirement of strength. Cost saving or flowing concrete or high slump concrete. To achieve the best results the mixer along with material should be rotated for at least 5 minute.

Dosage and Usage: Generally dosed 0.5-2.0% by weight of cement or above depending on climatic situation. Royal HR is used in flowing concrete. Pumping concrete as well as industrial and commercial flooring.

Technical Data:

Colour	-	Brown Colour
Form	-	Liquid
PH Value	-	7±1
Chloride Content	-	<0.5%
Air Concrete	-	<1%
Shelf life	-	1 year
Storage	-	Store it under shade
Chemical base	-	Sulphonate Naphthalene formaldehyde
Packing	-	250 kgs Drums
Health & Safety	-	Non-toxic, non-flammable and non hazardous and eco friendly

IMPORTANT

The product are manufactured under stringent quality standard specification and guaranteed against any manufacturing defect based our practical experience and exposure, and are believed to be most appropriate and correct. But no liability can be accepted by us as the condition of use of such products are beyond our control. The user is expected to check, the suitability of particular product for his intended uses.